

VOLVO PENTA GENSET ENGINE

TAD1640GE

432 kW (588 hp) at 1500 rpm, 480 kW (653 hp) at 1800 rpm, acc. ISO 3046

AREF DIESEL PARTS
تلفن: ۰۲۱-۸۸۸۸۸۸۸۸، ۰۲۱-۸۸۸۸۸۸۸۸
WWW.AREFDIESEL.COM

The TAD1640GE is a powerful, reliable and economical Generating Set Diesel Engine built on the dependable in-line six design.

Durability & low noise

Designed for easiest, fastest and most economical installation. Well-balanced to produce smooth and vibration-free operation with low noise level.

To maintain a controlled working temperature in cylinders and combustion chambers, the engine is equipped with piston cooling. The engine is also fitted with replaceable cylinder liners and valve seats/guides to ensure maximum durability and service life of the engine.

Low exhaust emission

The state of the art, high-tech injection and charging system with low internal losses contributes to excellent combustion and low fuel consumption.

The TAD1640GE complies with EU Stage 2 emission regulations.

Easy service & maintenance

Easily accessible service and maintenance points contribute to the ease of service of the engine.

Technical description

Engine and block

- Optimized cast iron cylinder block with optimum distribution of forces without the block being unnecessarily heavy.
- Wet, replaceable cylinder liners
- Piston cooling for low piston temperature and reduced ring temperature
- Tapered connecting rods for reduce risk of piston cracking
- Crankshaft induction hardened bearing surfaces and fillets with seven bearings for moderate load on main and high-end bearings
- Case hardened and Nitrocarburized transmission gears for heavy duty operation
- Keystone top compression rings for long service life
- Viscous type crankshaft vibration dampers to withstand single bearing alternator torsional vibrations
- Replaceable valve guides and valve seats
- Over head camshaft and four valves per cylinder

Lubrication system

- Full flow oil cooler



AREF DIESEL PARTS
تلفن: ۰۲۱-۸۸۸۸۸۸۸۸، ۰۲۱-۸۸۸۸۸۸۸۸
WWW.AREFDIESEL.COM

Features

- Maintained performance, air temp 40°C
- Tropical cooling system (55°C)
- Fully electronic with Volvo Penta EMS 2
- Dual frequency switch (between 1500 rpm and 1800 rpm)
- High power density
- Emission compliant
- Low noise levels
- Gen Pac configuration

- Full flow disposable spin-on oil filter, for extra high filtration
- The lubricating oil level can be measured during operation
- Gear type lubricating oil pump, gear driven by the transmission

Fuel system

- Non-return fuel valve
- Electronic unit injectors
- Fuel prefilter with water separator and water-in-fuel indicator / alarm
- Gear driven low-pressure fuel pump
- Fine fuel filter with manual feed pump and fuel pressure switch
- Fuel shut-off valve, electrically operated

Cooling system

- Efficient cooling with accurate coolant control through a water distribution duct in the cylinder block. Reliable sleeve thermostat with minimum pressure drop
- Gear driven, maintenance-free coolant pump with high degree of efficiency
- Coolant filter as standard

Turbo charger

- Efficient and reliable turbo charger
- Extra oil filter for the turbo charger

Electrical system

- Engine Management System 2 (EMS 2), an electronically controlled processing system which optimizes engine performance. It also includes advanced facilities for diagnostics and fault tracing
- The instruments and controls connect to the engine via the CAN SAE J1939 interface, either through the Control Interface Unit (CIU) or the Digital Control Unit (DCU). The CIU converts the digital CAN bus signal to an analog signal, making it possible to connect a variety of instruments. The DCU is a control panel with display, engine control, monitoring, alarm, parameter setting and diagnostic functions. The DCU also presents error codes in clear text.
- Sensors for oil pressure, oil temp, boost pressure, boost temp, coolant temp, fuel temp, water in fuel, fuel pressure and two speed sensors.

AREF DIESEL PARTS
تلفن: ۰۲۱-۸۸۸۸۸۸۸۸، ۰۲۱-۸۸۸۸۸۸۸۸
WWW.AREFDIESEL.COM

**VOLVO
PENTA**

TAD1640GE



Technical Data

General

Engine designation	TAD1640GE	
No. of cylinders and configuration	in-line 6	
Method of operation	4-stroke	
Bore, mm (in.)	144 (5.67)	
Stroke, mm (in.)	165 (6.50)	
Displacement, l (in ³)	16.12 (984)	
Compression ratio	17.5:1	
Dry weight, kg (lb)	1480 (3263)	
Dry weight with Gen Pac, kg (lb)	1910 (4211)	
Wet weight, kg (lb)	1550 (3417)	
Wet weight ith Gen Pac, kg (lb)	2020 (4453)	

Performance

	1500 rpm	1800 rpm
with fan, kW (hp) at:		
Prime Power	393 (534)	431 (586)
Max Standby Power	432 (588)	480 (653)

Lubrication system

	1500 rpm	1800 rpm
Oil consumption, liter/h (US gal/h) at:		
Prime Power	0.10 (0.026)	0.10 (0.026)
Max Standby Power	0.10 (0.026)	0.11 (0.029)
Oil system capacity incl filters, liter	48	

Fuel system

	1500 rpm	1800 rpm
Specific fuel consumption at:		
Prime Power, g/kWh (lb/hph)		
25 %	227 (0.368)	244 (0.396)
50 %	202 (0.327)	210 (0.340)
75 %	194 (0.314)	202 (0.327)
100 %	194 (0.314)	200 (0.324)
Max Standby Power, g/kWh (lb/hph)		
25 %	221 (0.358)	233 (0.378)
50 %	200 (0.324)	206 (0.334)
75 %	194 (0.314)	201 (0.326)
100 %	195 (0.316)	199 (0.323)

Intake and exhaust system

	1500 rpm	1800 rpm
Air consumption, m ³ /min (cfm) at:		
Prime Power	31 (1095)	40 (1413)
Max Standby Power	33 (1165)	42 (1483)
Max allowable air intake restriction, kPa (In wc)	5 (20.1)	5 (20.1)
Heat rejection to exhaust, kW (BTU/min) at:		
Prime Power		340 (19335)
Max Standby Power	327 (18596)	373 (21212)
Exhaust gas temperature after turbine, °C (°F) at:		
Prime Power	445 (833)	415 (779)
Max Standby Power	455 (851)	435 (815)
Max allowable back-pressure in exhaust line, kPa (In wc)	10 (40.2)	10 (40.2)
Exhaust gas flow, m ³ /min (cfm) at:		
Prime power	72.0 (2543)	87.0 (3072)
Max Standby Power	78.0 (2755)	93.0 (3284)

Cooling system

	1500 rpm	1800 rpm
Heat rejection radiation from engine, kW (BTU/min) at:		
Prime Power		28 (1592)
Max Standby Power	24 (1365)	28 (1592)
Heat rejection to coolant kW (BTU/min) at:		
Prime Power		166 (9440)
Max Standby Power	162 (9213)	177 (10066)
Fan power consumption, kW (hp)	8 (11)	14 (19)

Standard equipment

Engine

- Automatic belt tensioner
- Lift eyelets

Flywheel

- Flywheel housing with conn. acc. to SAE 1
- Flywheel for 14" flex. plate and flexible coupling
- Vibration dampers

Engine suspension

- Fixed front suspension

Lubrication system

- Oil dipstick
- Full-flow oil filter of spin-on type
- By-pass oil filter of spin-on type
- Oil cooler, side mounted
- Low noise oil sump

Fuel system

- Fuel filters of disposable type
- Electronic unit injectors
- Pre-filter with water separator

Intake and exhaust system

- Air filter with replaceable paper insert
- Air restriction indicator
- Air cooled exhaust manifold
- Connecting flange for exhaust pipe
- Exhaust flange with v-clamp
- Turbo charger, low right side

Cooling system

- Tropical radiator incl intercooler
- Gear driven coolant pump
- Fan hub
- Thrust fan
- Fan guard
- Belt guard

Control system

- Engine Management System (EMS) with CAN-bus interface SAE J1939
- CIU, Control Interface Unit

Alternator

- Alternator 60A / 24 V

Starting system

- Starter motor, 6.0kW, 24 V
- Connection facility for extra starter motor

Instruments and senders

- Temp.- and oil pressure for automatic stop/alarm 103°C


Other equipment

- Expandable base frame

Engine Packing

- Plastic warpping

- 1) must be ordered, se order specification
- optional equipment or not applicable
- included in standard specification



A* = 1587 mm / 62.5 in

B* = 1120 mm / 44.1 in

C* = 1976 mm / 77.8 in

D = 2296 mm / 90.5 in (During transport)

D = Max 3311 mm / 130.5 in

* Including radiator and intercooler

Note! Not all models, standard equipment and accessories are available in all countries.

All specifications are subject to change without notice.

The engine illustrated may not be entirely identical to production standard engines.

Power Standards

The engine performance corresponds to ISO 3046, BS 5514 and DIN 6271. The technical data applies to an engine without cooling fan and operating on a fuel with calorific value of 42.7 MJ /kg (18360 BTU/lb) and a density of 0.84 kg/liter (7.01 lb/US gal), also where this involves a deviation from the standards. Power output guaranteed within 0 to +2% att rated ambient conditions at delivery. Ratings are based on ISO 8528. Engine speed governing in accordance with ISO 3046/IV, class A1 and ISO 8528-5 class G3

Exhaust emissions

The engine complies with EU stage 2 emission legislation according to the Non Road Directive EU 97/68/EEC. The engine also complies with TA-luft -50% exhaust emission regulations.

Rating Guidelines

PRIME POWER rating corresponds to ISO Standard Power for continuous operation. It is applicable for supplying electrical power at variable load for an unlimited number of hours instead of commercially purchased power. A10 % overload capability for governing purpose is available for this rating.

MAXIMUM STANDBY POWER rating corresponds to ISO Standard Fuel Stop Power. It is applicable for supplying standby electrical power at variable load in areas with well established electrical networks in the event of normal utility power failure. No overload capability is available for this rating.

1 hp = 1 kW x 1.36

Information

For more technical data and information, please look in the Generating Set Engines Sales Guide.

VOLVO PENTA

AB Volvo Penta

SE-405 08 Göteborg, Sweden
www.volvopenta.com