



Lovol 1000 Nature gas engine - Genset

Inheriting from the leading European technology -Perkins, Lovol 1000 series provides professional power solution for genset, marine, water pump and agricultural equipment etc.

Important Features

- Adopting the electronic control multi-point injection and theoretic air and fuel ratio combustion strategy, the power performance and acceleration performance of nature gas engine are much higher than that of single-point injection and lean burn engine.
- The main maintenance parts, such as oil filter, air filter, pressure reducing valve and ignition coil, are all mounted in the right side, while the inlet and outlet in the left side (facing the fan), which brings the convenience to the maintenance.
- The adoption of the world advanced multi-point electronic fuel injection system not only brings the lower gas consumption and better economy, but also the higher emission standard.









-

Lovol 1000 Nature gas engine - Genset

| Item # | 1004NG | 1006NG | 1004NG | 1006NG |
|------------------------|---|--------------|---------------|---------------|
| Speed - rpm | 1500 | 1500 | 1800 | 1800 |
| Rated power - kW | 30 | 40 | 35 | 45 |
| Standby power - kW | 33 | 42 | 38 | 47 |
| Compression ratio | 16.5 : 1 | 17.5 : 1 | 17.5 : 1 | 17.5 : 1 |
| Noise - dB(A) | 92 | 92 | 94 | 94 |
| Dimension - mm | 1150*810*980 | 1150*810*980 | 1430*900*1000 | 1430*940*1000 |
| Bore * Stroke - mm | 100*127 | 100*127 | 100*127 | 100*127 |
| Displacement - L | 3.99 | 3.99 | 5.99 | 5.99 |
| Governor type | Electronic | Electronic | Electronic | Electronic |
| Governing rate | ≦1% | ≦1% | ≦1% | ≦1% |
| Oil pressure - Mpa | 0.34-0.45 | 0.34-0.45 | 0.34-0.45 | 0.34-0.45 |
| Configuration | In-line, direct injection, water-cooled | | | |
| Rotation of crankshaft | Counter-clockwise – viewed from flywheel side | | | |
| Cylinder number | 4 | 4 | 6 | 6 |
| Ignition system | Natural | Natural | Natural | Natural |

Standard Accessories

- 24V electric system (12V optional)
- S.A.E. 3 flywheel housing
- 10" & 11.5" flywheel
- Fuel, air and oil filter
- mmala/ • Qualification certificate, handbook & service manual
- 24V start motor, alternator and solenoid

Separate fan

Cold start aid

• Engine front support

• Radiator - fan guard & front guard included

• Oil pressure and water temperature alarm switch & sensor (2 in 1) in accordance with VDO parameter